40 YEARS IN HUMIDIFICATION

New electric humidifiers ELMC – RTH series

New models ELMC













Devatec ELMC New Model



Stronger door fixation with inserts.



- Control voltage in 24VAC
- Stronger fixation on the cabinet with screws



- New cabinet design with better access to electrical compartment
 - Review of the electrical installation with slotted trunking and separation into 2 rails :
 - 1 internal control rail
 - 1 customer connection rail
 - On/off button on the unit Right side
 - Built-in transformer 2x115V / 2x12V (for control 24VAC), (possibility to have 115V control voltage)
- Improved natural ventilation with more openings
- No LED power-on indicator



New models RTH-LC







Devatec RTH-LC New Model

I

Standard safety thermoswitch on each tank

Position of the water level detector on the front for much easier access

Solenoid valves for drain and inlet water in 24VAC



 Stronger fixation on the cabinet with screws



 Stronger door fixation with inserts.



New cabinet design with better access to electrical compartment

Review of the electrical installation with slotted trunking and separation into 2 rails:

1 internal control rail

1 customer connection rail

Built-in transformer 2x115V / 2x12V (for control 24VAC), (possibility to have 115V control voltage)

• On/off button on the unit Right side

 Change of position of the fan to bottom part of the cabinet for improved ventilation

No LED power-on indicator



New models RTH-HC








Devatec RTH-HC New Model


000



 Standard safety thermoswitch on each tank

Standard FLOAT type level detector for all types of water,





 Stronger fixation on the cabinet with screws

Stronger door fixation with inserts.

 Reinforced cabinet and easier access to holes for wall mounting New cabinet design with better access to electrical compartment

Review of the electrical installation with slotted trunking and separation into 2 rails:

1 internal control rail

1 customer connection rail

Built-in transformer 2x115V / 2x12V (for control 24VAC), (possibility to have 115V control voltage)

On/off button on the unit Right side

 Change of position of the fan to bottom part of the cabinet for improved ventilation

• No LED power-on indicator





Option changes

Support chair:

Possible to be sold in kit form (reducing shipping costs). Stainless steel support chair leg, stainless steel brushed finish Reduction of the price of the option

Cooling system:

Factory assembly
Better cooling efficiency (65°C max measured on manual drain)
Reduction of the price of these options.
Available for ELMC, RTH-LC and RTH series.

Transformer option:

1 code for option instead of 4 different ones (380-600V)

Offshore option:

No offshore range, but an offshore option valid for all models, including


- Ferrite,
- One 690VAC transformer fitted.





Flexible water supply hose and 1m drain hose not included in unit price anymore.

Available in OPTION (only drain and steam hoses clamps supplied)





HUMIDITY MADE IN NORMANDY



185, Boulevard des Frères Rousseau - Offranville 76550





